## **AMENDMENTS TO THE CLAIMS**

€3

## Claims 1-4 (Canceled)

Claim 5 (Currently Amended) An in-line roller skate for racing, comprising:

a footwear having a sole on the bottom thereof, said sole having a heel-piece zone and a toe juncture area corresponding to an area of a foot where the toes of the foot join the foot;

a chassis supporting at least four wheels including a front wheel and a second wheel immediately behind said front wheel, said front wheel and said second wheel being located in a front zone of said chassis;

at least first and second binding points on said sole <u>attaching for attachment of said sole</u> to said chassis, said first binding point being positioned in proximity of said heel-piece zone of said sole, and said second binding point being positioned approximately in <u>the a-toe</u> juncture area of said sole;

fasteners for joining said footwear to said chassis at said first and second binding points, said second binding point being located between said front wheel and said second wheel;

wherein said at least four wheels are solely wheels having a diameter of at least 100 mm; and

wherein a height of said front zone of said chassis in relation to a ground contact plane of said at least four wheels is substantially equal to said diameter of said at least four wheels.

wherein a center to center distance between said first and second binding points is between 170 mm and 210 mm.

## Claim 6 (Canceled)

Claim 7 (Currently Amended) The in-line roller skate of claim 6 5, wherein the center to center distance between said first and second binding points is 195 mm.